

170-03062



Article Number: 170-03062

Description: Braided Sleeving, Aluminum Laminated Fiberglass, .5 Dia, AL/GF, Silver, 100 ft/reel

Base Data	Local Order Number	170-03062
	Type	BSHTTST12SR
	Color	Silver (SR)
	Features and Benefits	<ul style="list-style-type: none"> • A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion. • Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments. • Cuts with ordinary scissors for fast, easy application.
	Quantity Per	reel
	Product Description	A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.
	Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, .5 Dia, AL/GF, Silver, 100 ft/reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		30.48m
Reel Length (imperial)		100.0ft
Bundle Diameter Max. (Imperial)		0.437"
Bundle Diameter Max. (Metric)		11.1mm
Nominal Diameter (Imperial)		1/2"
Nominal Diameter (Metric)		12.7mm
Material and Specifications		Material
	Material Shortcut	AL
	Flammability	non flammable
	Operating Temperature	-76°F to +491°F (-60°C to +255°C)
	ROHS Compliant	Yes

170-03062



Logistic and Packaging		
	Package Quantity (Imperial)	100ft
	Package Quantity (Metric)	30.48m
	Customs Number(Schedule B)	7019901000
	Weight (imperial)	2.55lbs
	Weight (Metric)	1.16kg