

KFM  
KFK025824



KFM-2/AH 3D 3C Lg

KFM has a sturdy all-metal construction with a sleek design, flexible arm and excellent light output suitable for a variety of industrial, laboratory, cosmetology and low-vision application. The flexibility of the neck assembly and patented internal spring 30" K-arm makes exact positioning easy. ~~Old item no: 17213G~~ (1.75X) optical-quality glass lens. Edge clamp mount. Color: light grey.



**Optic**

Color of reflector	White
Material of diffuser	Polycarbonate
Material of reflector	P C
Primary Lens (D)	3
Working distance (mm)	333
Magnification (X)	1.75

**Electrical data**

Maximum frequency (Hz)	60
Minimum frequency (Hz)	50
Maximum voltage (V)	120
Voltage from (V)	100

**Body**

Body color	Grey
Body material	Aluminum

**Technical data**

IP classification	20
-------------------	----

**Lightsource**

Number of lamps	1
Lamp power (W)	22
Lamp base	G10Q
CRI and/or Color Temperature	4100K
Lightsource	T9

**Dimensions**

Net weight (kg)	4,22
Gross weight (lb.)	10
Arm length (in.)	30

**Termination**

Cord length (ft)	6
Mounting	Edge clamp

**Ballast**

Type of Ballast	High frequency
-----------------	----------------