

151-06500



Article Number: 151-06500

Description: Dual Swivel Saddle Spacer for T50-T250, .25"–3.0" Bundle Diameter, Black, PA66HS, 2200/pkg

Base Data	
Local Order Number	151-06500
Type	DSWS4
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • "H" profile of the saddles allows for broad surface contact with the bundle, which minimizes pinching and crushing of the bundle. • Swivels in 360 degree motion to accommodate any area. • Accommodates T50-T250 ties to handle both light duty and heavy duty applications.
Quantity Per	bag
Product Description	These saddle spacers are installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc.) to separate and prevent chafing and wear. The mounts can be easily rotated by hand, allowing the bundles to be crossed and rotated at any angle. Cable ties, which secure the bundles, are used with the mounts. The dual swivel saddle spacers accommodate cable ties up to 1/2" wide
Short Description	Dual Swivel Saddle Spacer for T50-T250, .25"–3.0" Bundle Diameter, Black, PA66HS, 2200/pkg
Product Dimensions	
Length L (Imperial)	0.91"
Length L (Metric)	23.6mm
Width W (Imperial)	0.8"
Width W (Metric)	20.3mm
Height H (Imperial)	0.7"
Height H (Metric)	18.0mm
Bundle Diameter Min. (Imperial)	0.3"
Bundle Diameter Min. (Metric)	6.0mm
Bundle Diameter Max. (Imperial)	3.0"
Bundle Diameter Max. (Metric)	76.0mm

151-06500

Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	POM
	Flammability	UL 94 HB
	Minimum Extraction Force (Imperial)	100.0lbs
	Minimum Extraction Force (Metric)	445N
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	2200
	Package Quantity (Metric)	2200Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	3.8kg