

3-Port USB 3.1 Gen 1 Portable Hub, USB-C to (x3) USB-A, with Gigabit Ethernet Port

MODEL NUMBER: **U460-003-3AG**



Highlights

- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- Supports true 10/100/1000 Mbps Ethernet network speeds
- Backward compatible with previous USB generations
- Fits easily into backpack, briefcase or laptop bag
- Plug-and-play—no software or drivers required

Package Includes

- U460-003-3AG 3-Port USB 3.1 Gen 1 Portable Hub
- Owner's manual

Description

The U460-003-3AG 3-Port USB 3.1 Gen 1 Portable Hub's built-in USB-C cable connects to your computer, laptop or tablet's USB-C port to give you three external USB-A ports and an RJ45 Gigabit Ethernet port. Not only does this hub enable you to access true 10/100/1000 Mbps Ethernet network speeds without the hassle and expense of installing an internal Ethernet card in your device, but it allows you to connect a wide range of USB devices, such as flash drives, external hard drives, DVD players, MP3 players and digital cameras.

The U460-003-3AG supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps—ten times faster than USB 2.0. It's backward compatible with previous USB generations, so you can continue using older peripherals while getting maximum high-speed performance from new devices.

The compact case fits easily into your backpack, briefcase or laptop bag to power USB-enabled devices wherever you are. No software or drivers are needed.

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum

Features

Connects Up to 3 USB-A Peripherals

- Ideal for flash drives, external hard drives, DVD players, MP3 players and digital cameras
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- Backward compatible with previous USB generations

RJ45 Gigabit Ethernet Port

- Supports true 10/100/1000 Mbps network speeds

Compact Case

- Fits easily into your backpack, briefcase or laptop bag



- Built-in USB-C cable is perfect for travel
- Plug-and-play—no software or drivers required

Specifications

ENVIRONMENTAL	
Storage Temperature Range	14 TO 167 F (-10 TO 75 C)
Relative Humidity	0% TO 85%
Operating Temperature	32 TO 122 F (0 TO 50 C)
CONNECTIONS	
Ports	4
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	(3) USB A (FEMALE)
Side B - Connector 2	RJ45 (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>