



Tripp Lite
 1111 West 35th Street
 Chicago, IL 60609 USA
 Telephone: +(773) 869 1234
 E-mail: saleshelp@tripplite.com

Model #: SS7415-15

16 outlet, 15-ft cord, 450 joule Power Strip with Surge Suppression

Highlights

- 16 outlets
- 15-ft. cord
- 48-in. length
- 450-joule rating



Description

The SS7415-15 4-ft. power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more. Includes 16 NEMA 5-15R output receptacles with 2.717-in. center-to-center spacing, 15-ft. AC line cord and adjustable mounting clips for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 450 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive gray housing with black output receptacles.

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 16 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: 4-ft. corded vertical/raceway power distribution strip

SURGE SUPPRESSION: 450 joules

Applications

- Offers outlet power distribution with surge suppression for multiple loads in equipment racks, computer rooms, workbenches and raceways in a variety of internetworking, telecommunications, audio/video and live sound applications.

Package Includes

- SS7415-15 Power Strip/Surge Suppressor
- Set of adjustable mounting clips
- Warranty information
- Instruction manual

Specifications

| | |
|-----------------------------|---|
| OVERVIEW | |
| Intended Application | Computer Networking, Industrial/Factory Floor |
| OUTPUT | |

| | |
|--------------------------------------|--|
| Frequency compatibility | 50 / 60 Hz |
| Output watts | 1800 |
| Circuit Breaker (amps) | 15 |
| Outlet quantity / type | 16 NEMA 5-15R |
| Outlet Type | NEMA 5-15R |
| Outlet spacing | 2.717-in. center-to-center spacing |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V |
| Input connection type | NEMA 5-15P |
| Input cord length (ft.) | 15 |
| Input cord length (m) | 4.57 |
| Voltage compatibility (VAC) | 120 |
| Maximum Surge Amps | 22000 |
| LEDS ALARMS & SWITCHES | |
| Switches | Combination AC circuit breaker and lighted 2-position power switch controls power to all outlets |
| Locking switch cover | Transparent locking switch cover |
| SURGE / NOISE SUPPRESSION | |
| AC suppression joule rating | 450 |
| UL1449 let through rating | 500V UL verified |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection | No |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| PHYSICAL | |
| Unit Dimensions (HWD/in) | 48 x 1.5 x 1.5 |
| Unit Dimensions (HWD/cm) | 121.92 x 3.81 x 3.81 |
| Mounting accessories included | Set of adjustable mounting clamps |
| Receptacle Color | Black |
| AC line cord color | Black |
| Outlets center to center measurement | 67mm |
| CERTIFICATIONS | |
| UL1449 3rd Edition (AC Suppression) | UL1449 3rd EDITION |

| | |
|--|---------------------------|
| UL1363 (Power Tap) | UL1363 |
| cUL / CSA (Canada) | cUL |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=1948.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.