## **HellermannTyton**

Article Number: 170-03056



Braided Sleeving, Aluminum Laminated Fiberglass, 1" Dia, AL/GF, Silver, 250 ft/bulk reel

Base Data		
	Local Order Number	170-03056
	Туре	BSHTTST10SRB
	Color	Silver (SR)
	Features and Benefits	<ul> <li>A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.</li> <li>Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.</li> <li>Cuts with ordinary scissors for fast, easy application.</li> </ul>
	Quantity Per	reel
	Product Description	A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.
	Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, 1" Dia, AL/GF, Silver, 250 ft/bulk reel
Product Dimensions		
	Length L (Imperial)	250.0ft
	Length L (Metric)	76.2m
	Reel Length (imperial)	250.0ft
	Bundle Diameter Max. (Imperial)	0.937"
	Bundle Diameter Max. (Metric)	23.8mm
	Diameter D (imperial)	1.0"
	Nominal Diameter (Imperial)	1"
	Nominal Diameter (Metric)	25.4mm
Material and Specifications		
	Material	Glass Fiber (GF)
	Material Shortcut	GF
	Flammability	non flammable

## 170-03056

## HellermannTyton

Material and Specifications	Operating Temperature	-76°F to +491°F (-60°C to +255°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	250ft
	Package Quantity (Metric)	76.2m
	Customs Number(Schedule B)	7019901000
	Weight (imperial)	11.25lbs
	Weight (Metric)	5.08kg