

# Datamate J-Tek Connectors

## Male Crimp Kit Reverse Fix

- Allows for further flexibility in system design.
- Part numbers are for a complete kit of a housing and the applicable number of contacts.
- Crimp contacts are rear insertable and replaceable.
- Mates with female Datamate J-Tek connectors with compatible Reverse Fix jackscrews.



DATAMATE J-TEK

REVERSE FIX		CALCULATION													
		<b>A</b>	$B + 12$												
		<b>B</b>	Total no. of contacts - 2												
		<b>C</b>	$B + 7$												
TOOLS		WIRE STRIPPING DETAILS													
<p><b>Recommended Crimp Tool</b> - M22520/2-01</p> <p><b>Positioner</b> - Z80-193</p> <p><b>Contact Insertion/Removal Tool</b> - Z80-280</p> <ul style="list-style-type: none"> <li>Spare contacts shown on following pages.</li> <li>Instruction sheets available at <a href="http://www.harwin.com/instructions">www.harwin.com/instructions</a>.</li> </ul>															
HOW TO ORDER															
<b>M80 - 5XX XX 05</b>															
<p><b>SERIES CODE</b></p> <table border="1"> <thead> <tr> <th colspan="2">TYPE</th> </tr> </thead> <tbody> <tr> <td><b>562</b></td> <td>Large Bore (22 AWG), Slotted Jackscrew</td> </tr> <tr> <td><b>563</b></td> <td>Small Bore (24-28 AWG), Slotted Jackscrew</td> </tr> <tr> <td><b>582</b></td> <td>Large Bore (22 AWG), Hex Socket Jackscrew</td> </tr> <tr> <td><b>583</b></td> <td>Small Bore (24-28 AWG), Hex Socket Jackscrew</td> </tr> </tbody> </table>		TYPE		<b>562</b>	Large Bore (22 AWG), Slotted Jackscrew	<b>563</b>	Small Bore (24-28 AWG), Slotted Jackscrew	<b>582</b>	Large Bore (22 AWG), Hex Socket Jackscrew	<b>583</b>	Small Bore (24-28 AWG), Hex Socket Jackscrew	<p><b>FINISH</b></p> <table border="1"> <tbody> <tr> <td><b>05</b></td> <td>Gold</td> </tr> </tbody> </table>		<b>05</b>	Gold
TYPE															
<b>562</b>	Large Bore (22 AWG), Slotted Jackscrew														
<b>563</b>	Small Bore (24-28 AWG), Slotted Jackscrew														
<b>582</b>	Large Bore (22 AWG), Hex Socket Jackscrew														
<b>583</b>	Small Bore (24-28 AWG), Hex Socket Jackscrew														
<b>05</b>	Gold														
		<p><b>TOTAL NO. OF CONTACTS</b></p> <p><b>04, 06, 08, 10, 12, 14, 20, 26, 34, 42, 50</b></p>													

All dimensions in mm.