

PART NUMBER SSI-LXMP059SRD

C

	REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
	Α	ADDED DIMS, NOTES AND UPDATED SPECS.	12.19.94
	В	E.C.N. #10122.	6.27.96
1	C	E.C.N. #10BRDR. & REDRAWN IN 3D.	1.7.02

ELECTRO-OPTICAL CH	HARACTERIS	TICS TA=25')	$I_f = 20mA$	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		660		nm	
FORWARD VOLTAGE		1.7	2.2	Vf	
REVERSE VOLTAGE	4.0			V_r	1 _r =100µA
AXIAL INTENSITY		25		mcd	$I_f = 20mA$
VIEWING ANGLE		110		2x theta	
EMITTED COLOR:	RED				
EPOXY LENS FINISH:	RED DIFFUSED				

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	100	mW
DERATE FROM 25°C	-1.2	mW/'C
OPERATING, STORAGE TEMP.	-40 TO +85	°C
SOLDERING TEMP.	+ 260	. C
2.0mm FROM BODY		3 SEC. MAX

* t<10µS

NOTES:

- 1. SSL-LX2573SRD, RED LED.
- 2. SSH-LXMP059-HSG, BLACK HOUSING.
- 3. SSH-LXMP059-BSG, BLACK BUSHING.

UNCONFIGURE FOR LARGE LA

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECI

REV. PART NUMBER

C SSI-LXMP059SRD

660nm SUPER RED RECTANGULAR PANEL INDICATOR,
RED DIFFUSED LENS.

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OF IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

1,25~3,00 [0,049~0,118]

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 11.5.92
PAGE: 1 OF 1
BC SCALE: N/A