

157-00106

Article Number: 157-00106



Description: Oval Shaped Stud Mount Ties, 6.6" Long, 50lb Tensile, Without Thumb Bar, PA66HS, Black, 1000/pkg

Base Data	Local Order Number	157-00106
	Type	T50SOSSB5-High-E-O-US
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Head allows for a .2" lateral adjustment on stud during installation.</li> <li>• Quick and easy installation ideal for manufacturing environment.</li> </ul>
	Quantity Per	bag
	Product Description	Oval Shaped Stud Mount's special design allows for a .2" (5.5mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools.
	Short Description	Oval Shaped Stud Mount Ties, 6.6" Long, 50lb Tensile, Without Thumb Bar, PA66HS, Black, 1000/pkg
Product Dimensions	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	225N
	Length L (Imperial)	6.6"
	Length L (Metric)	167.0mm
	Fixation Method	Weld Stud Fixing
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Width W (Imperial)	0.2"
	Width W (Metric)	5.0mm
	Bundle Diameter Min. (Imperial)	0.04"
	Bundle Diameter Min. (Metric)	1.0mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
Stud Size (Imperial)	0.2"	

157-00106



Product Dimensions	Stud Size (Metric)	5.0 mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	bag